

AZ-8801 / 8803 AT A GLANCE

K TYPE THERMOMETER ! ECONOMICAL & ACCURATE ! SELECT FROM SINGLE OR DUAL INPUT MODELS !

FEATURE

K type thermocouple.

8801:Single input T1 only.

8803:Dual input T1, T2, T1-T2.

0.1 and 1.0degree switchable resolution (8801).

Maximum reading memory.

Low battery indicator.

Hold function.

C/F units switchable.

Auto power off (20min), disable sleep mode.

Temperature coefficient:0.1 times the applicable accuracy specification per from 0 to 18 and 28 to 50.

Meter includes one K-type thermocouple probe, 9V battery, Manual, Hard plastic case.

SPECIFICATION

Temperature range :	-50~1300	181mm x 71mm
Measurement range :	-50~1300(-58~2000)	Dimensions : x38mm
Operation temperature :	0~50 (0~85%RH, non-cond)	(7.1" x2.8" x1.5")
Sampling rates :	2.5 per second	Accuracy (18~28) ambient temperature :
Battery :	9 Volt , battery life : 200 hours	-50~1000 ±(0.3% rdg + 1)
Display :	37mm x 42mm LCD, Maximum reading 1999	1000~1300±(0.5% rdg + 1)
		-58~1800 ±(0.3% rdg + 2)
		1800~2000±(0.5% rdg + 2)
		Switchable resolution :
		0.1 and 1.0 degree (model:8801)
		1.0 degree (model:8803)