



This all-in-one tester incorporates continuity, insulation resistance, RCD, earth loop impedance, phase loop impedances, earth resistance and phase rotation tests.

This unit is smaller and more compact than other machines on the market, which makes it very comfortable to use in confined and hazardous areas.

The Veritest stores test results in its internal memory and downloads to a P.C. via optional software and accessories.

The Veritest is supplied complete with test leads, a protective carry case and user guide as standard. A full manual is available for free download at www.martindale-electric.co.uk.

ENVIRONMENT

Environmental working conditions

Reference temperature: 23° ± 5°C

Working temperature: -10°C – 50 °C

Relative humidity allowed: <80%

Storage temperature: -20 – 60 °C

Storage humidity: <80%

Due to policy of continuous development, Martindale Electric reserves the right to alter equipment specification and description outlined in this document without prior notice. No part of this document shall be deemed to be part of any contract for the equipment unless specifically referred to as an inclusion within such contract. © Martindale Electric Co. Ltd. 2001

SPECIFICATIONS

SHEET 1 OF 2

Accuracy is indicated as [% of reading + number of digits]. It refers to the atmospheric conditions listed previously.

CONTINUITY:

Test mode	Range	Resolution	Accuracy
AUTO, R+, R-	0.01-19.99Ω	0.01Ω	±(2%rdg+2dgt)
	20.0-99.9Ω	0.1Ω	
Timer Mode	0.01-9.99Ω	0.01Ω	±(2%rdg+2dgt)

Test current: >200mA DC up to 16Ω (include the resistance of the calibration) 40mA DC from 16Ω to 99.9Ω **resolution:** 1mA

Open circuit Test Voltage: 9V

Live Circuit Warning: Yes

Timer: test duration 10-999 seconds

INSULATION TESTS

Rated Test Voltage	Measurable Range MΩ	Resolution	Accuracy
50V	@Rated Test Voltage		
	0.05-19.99 MΩ	0.01MΩ	±(2%rdg+2dgt)
	20.0-49.9 MΩ	0.1MΩ	±(2%rdg+2dgt)
100V	50.0-99.9 MΩ	0.1MΩ	±(5%rdg+2dgt)
	0.10-19.99 MΩ	0.01MΩ	±(2%rdg+2dgt)
	20.0-99.9 MΩ	0.1MΩ	±(2%rdg+2dgt)
250V	100.0-199.9 MΩ	0.1MΩ	±(5%rdg+2dgt)
	0.23-19.99 MΩ	0.01MΩ	±(2%rdg+2dgt)
	20.0-199.9 MΩ	0.1MΩ	±(2%rdg+2dgt)
500V	200-249 MΩ	1MΩ	±(2%rdg+2dgt)
	250-499 MΩ	1MΩ	±(5%rdg+2dgt)
	0.25-19.99 MΩ	0.01MΩ	±(2%rdg+2dgt)
1000V	20.0-199.9 MΩ	0.1MΩ	±(2%rdg+2dgt)
	200-499 MΩ	1MΩ	±(2%rdg+2dgt)
	500-999 MΩ	1MΩ	±(5%rdg+2dgt)
1000V	1000-1999 MΩ	1MΩ	±(5%rdg+2dgt)
	0.90-19.99 MΩ	0.01MΩ	±(2%rdg+2dgt)
	20.0-199.9 MΩ	0.1MΩ	±(2%rdg+2dgt)
1000V	200-999 MΩ	1MΩ	±(2%rdg+2dgt)
	1000-1999 MΩ	1MΩ	±(5%rdg+2dgt)

Automatic selection of the measuring range

Open circuit voltage: Rated test voltage -0% +10%

Short circuit current: <3.0mA - 500V

<2.0mA - 50V, 100V, 250V, 1000V

Test current on load: >1mA@V_{Test} across R_{load}=(1000 x V_{Test})Ω

If the instrument measures a voltage higher than 30V, the instrument does not perform the test.

Martindale Electric Company Ltd.

Metrohm House, Penfold Trading Estate, Imperial Way, Watford, WD24 4YY. Tel: 01923 441717 Fax: 01923 446900

E-mail: sales@martindale-electric.co.uk Web site: <http://www.martindale-electric.co.uk>

RCD

Type of RCD: AC, A

Range of phase to earth voltage: (100 - 265) V

Rated Tripping Current ($I_{\Delta N}$): 10mA, 30mA, 100mA, 300mA, 500mA

Test frequency: 50Hz \pm 0.5 Hz

TRIPPING TIMES

Test	Range	Resolution	Accuracy
$\frac{1}{2} I_{\Delta N}, I_{\Delta N}$	0-999ms	1ms	$\pm(2\%rdg+2dgt)$
$2 I_{\Delta N}$	0-200ms general	1ms	$\pm(2\%rdg+2dgt)$
	0-250ms selective	1ms	$\pm(2\%rdg+2dgt)$
$5 I_{\Delta N}$ RCD(*)	0-50ms general	1ms	$\pm(2\%rdg+2dgt)$
	0-160ms selective	1ms	$\pm(2\%rdg+2dgt)$

(*) For RCD type A 500mA, the MAN x5 and AUTO tests are not available. The Ramp test measures tripping current

CONTACT VOLTAGE

Measuring range(V) Resolution(V) Accuracy

0 - 2U _t Lim	0.1	-0%,+(10%rdg+2dgt)
U _t Lim (U _L): 25V or 50V		

TRIPPING CURRENT FOR RCD TYPE A AND AC

RCD with $I_{\Delta N} \leq 10mA$

Type RCD	Range $I_{\Delta N}$ (mA)	Resolution(mA)	Accuracy $I_{\Delta N}$
AC	(0.5 - 1.4) $I_{\Delta N}$	0.1 $I_{\Delta N}$	-0%, +10% $I_{\Delta N}$
A	(0.5 - 2.4) $I_{\Delta N}$		

RCD with $I_{\Delta N} \geq 10mA$

Type RCD	Range $I_{\Delta N}$ (mA)	Resolution(mA)	Accuracy $I_{\Delta N}$
AC	(0.5 - 1.4) $I_{\Delta N}$	0.1 $I_{\Delta N}$	-0%, +10% $I_{\Delta N}$
A	(0.5 - 2) $I_{\Delta N}$		

AC VOLTAGE:

Electrical Syst	Range(V)	Resolution(V)	Accuracy
Single-phase	0 - 265	1	$\pm(2\% rdg + 2 dgt)$
2 or 3 - phase	0 - 460	1	$\pm(5\% rdg + 2 dgt)$

FREQUENCY:

Range(V) HZ	Resolution HZ	Accuracy
15.3 - 99.9 Hz	0.1 HZ	$\pm(0.1\% rdg + 1 dgt)$

LINE IMPEDANCE

(LOOP Z_S/I_K PHASE TO PHASE OR PHASE TO NEUTRAL)

Test mode	Range	Resolution	Accuracy
(P-P & P-N)	0.03-19.99 Ω (0.01 Ω Res)		$\pm(5\% rdg + 2 dgt)$
	20.0-199.9 Ω (0.1 Ω Res)		$\pm(5\% rdg + 2 dgt)$
PSC	1-999A		
	1.0-20.0KA		

Test voltage: V_{PN} 100V - 265V 50Hz + 0.5 Hz
V_{PP} 100V - 460V 50Hz + 0.5 Hz

Max peak test current: 100V 3.17A test duration: 80ms
230V 6.64A test duration: 40ms
400V 11.5A test duration: 40ms

Accuracy current measurement: $\pm 10\% I_{max}$ Pk

PHASE EARTH IMPEDANCE (LOOP Z_S/I_K)

Range	Resolution	Accuracy
0.03-19.99 Ω	(0.01 Ω Res)	$\pm(5\%rdg+2dgt)$
20.0-199.9 Ω	(0.1 Ω Res)	$\pm(5\%rdg+2dgt)$
200-1999 Ω	(1 Ω Res)	$\pm(5\%rdg+2dgt)$
PFC	1-999A, 1.0-20.0KA	

Max peak test current: 100V 3.17A Test duration: 80ms
230V 6.64A Test duration: 40ms

Accuracy current measurement: $\pm 10\% I_{max}$ Pk

Test voltage: V_{PE} 100V - 265V 50Hz +0.5 Hz

NON TRIP EARTH LOOP TEST: (R_{A15MA})

Measuring range	Resolution	Accuracy
1-1999 Ω	1 Ω Res	$\pm(5\%rdg+2dgt)$
PFC	1-999 Amps, 1.0-20.0KA	
Test current	15mA	

Battery type: 6x1.5V LR6-AA-AM3-MN1500

Low battery indication: Yes

Battery life: About 40 hrs in stand-by or 500 Continuity tests or 250 Insulation tests 500V/500k or

1000 LOOP/RCD/PHASE SEQUENCE TESTS

Weight: (batteries included) 1000gm

Dimensions: 222mm(L) x 162mm(W) x 57mm(D)

Phase Rotation Test: graphic display of phase sequence

Memory Slots For Saved Tests: 350

Display Features: LCD custom

Interface optical: RS232 to print or to download the tests

SAFETY STANDARDS

The instrument complies with: EN 61010-1 + A2 (1997), EN61557, EN61326-1 (1997) + A1 (1998).

Insulation: Class 2, double insulation

Pollution degree: 2

Inside use: max altitude - 2000m

Overvoltage category: CAT III 460V~ P-N-E / 265V~ to earth