

MS2138R AC/DC DIGITAL CLAMP METER (True RMS)



FEATURES

- Conform to the IEC1010-1 & IEC1010-1-032 standard
- Double insulation (protection class 600V CAT III and pollution de
- Display: 3999 counts and 42 segments bar graph
- Auto/Manual range
- True RMS for AC voltage and current
- Auto zero key for DCA
- Data hold function
- MAX/MIN function
- Back light function
- Jaw lighting
- Auto power off
- DCV: 4/40/400V±0.8%, 1000V±1.0%
- ACV: 4/40/400V±1.0%, 700V±1.2%
- DCA: 400/1000A±3.0%
- ACA: 400/1000A<600A±2.5%, ≥600A±3.0%
- Resistance: 400/4k/40k/400k/4MΩ±1.0%, 40MΩ±2.0%
- Continuity test
- Diode test
- Frequency: 40Hz to 100kHz±0.1% (from test terminal), 40Hz to 400Hz±0.1% (from current clamp)
- MAX. diameter for conductor: Φ42mm
- Secondary injection molding case
- SMT application
- Dimension: 225mm x 86mm x 33mm
- Power: 1.5V (AAA) x 3
- Weight: 320g



test4less

Test4Less
Century Road
High Carr Business Park
Newcastle-Under-Lyme
Staffordshire
ST5 7UG
Telephone: 0800 040 7477
www.test4less.co.uk