

# MultiServicer

A complete solution to testing of safety on machines, switchgears, controlgears, and portable electrical appliances

MI 2170 - Machine, Switchgear, PAT Tester

Three testers in one - its your choice

\* also available MI 2171 - Machine Tester only



Measurements in accordance with:

- |                         |  |
|-------------------------|--|
| <b>IEC 60204</b>        | Electrical equipment of machines.  |
| <b>IEC 60439-1</b>      | Switchgear and controlgear assemblies.   |
| <b>IEC 60755</b>        | Residual current operated protected devices.                                   |
| <b>IEC 60598-1</b>      | Luminaires.  |
| <b>VDE 701, VDE 702</b> | Repair and modification inspections and repeat tests of electrical appliances. |
| <b>IEC 50144-1</b>      | Safety of hand-held electric motor operated tools.                             |

## New for Multi Applications

- electrical service engineers
- switchgear / safety engineers
- electrical maintenance engineers



Final test on a portable appliance in a service workshop



Testing of safety in a construction site on a switchgear



Complete testing of safety on machines (at initial installation or on periodic basis)

**Automatic test:** One-man operation by remote probe






# Key Features

All accessories are placed in the protective bag

Large custom LCD, PASS / FAIL LEDs

Fuses for additional protection of the test socket



RS 232 port for downloading data on PC, and print-out of test reports

Quick reference guide for testing

Withstanding voltage test  
2500 V AC / 250 VA;  
1000 V AC / 500 VA

Multifunction test sockets

Robust waterproof case

Selection of functions by large and robust selection switch

Memory and display commands

## Technical specification

Function	Measuring range;	Accuracy	MI 2170	MI 2171
<b>Withstanding voltage test 2500 V AC / 250 VA</b> Trip-out current / time	0 - 3000 V	± (5% + 5 dig.)	✓	
<b>Withstanding voltage test 1000 V AC / 500 VA</b> Trip-out current / time	0 - 1500 V	± (5 % + 5 dig.)	✓	✓
<b>Insulation resistance test 500 V DC (Hi and Lo terminal)</b> Test current Primary field of use: testing of machines, switchgears	0 - 19.99 MΩ min. 1 mA at 500 kΩ	± (5 % + 5 dig.)	✓	✓
<b>Voltage drop test / Continuity test 10 A (*)</b> (Hi and Lo terminal) Test current Primary field of use: testing of machines	0 - 11.99 V 0 - 1.999 Ω >10 A at R <330 mΩ	± (5 % + 5 dig.) ± (5 % + 5 dig.)	✓	✓
<b>Discharge time test 60 V, 120 V (Hi and Lo terminal)</b> Input resistance	0 - 9.9 s 48 MΩ	± (5 % + 3 dig.)	✓	✓
<b>Voltage measurement</b>	0 - 450 V TRMS	± (2 % + 3 dig.)	✓	✓
<b>Functional test</b>	0 - 15.99 A	± (5 % + 3 dig.)	✓	✓
<b>Continuity test 10 A (*)</b> (on shuko plug) Test current Primary field of use: testing of appliances	0 - 1.999 Ω >10 A at R <330 mΩ		✓	
<b>Continuity test 200 mA</b> Test current	0 - 19.99 Ω >200 mA	± (5 % + 5 dig.)	✓	
<b>Insulation resistance test 500 V DC (on shuko plug)</b> Test current Primary field of use: testing of appliances	0 - 19.99 MΩ min. 1 mA at 500 kΩ	± (5 % + 5 dig.)	✓	
<b>Substitute Leakage</b> Open circuit voltage	0 - 19.99 mA 40 V	± (5 % + 5 dig.)	✓	
<b>Touch Leakage Current</b> Probe resistance	0 - 1.99 mA 1.8 kΩ	± (5 % + 5 dig.)	✓	
<b>Differential Leakage Current</b>	0 - 19.99 mA	± (5 % + 5 dig.)	✓	✓

(\*) Automatic test

## General specification

Power supply	230 V AC (optional 110 V)
Memories	50 locations
Degree of protection (closed case)	IP 54
Protection classification	I
Pollution category	2
Overvoltage category	Cat III 300 V
Compensation of test leads	yes
Dimensions (w x h x l)	345 × 160 × 335 mm
Weight (without accessories)	9.5 kg

## Standard set

Order No. **MI 2170, MI 2171**



- Instrument
- HV test lead
- Test lead (black), 2 m
- Test lead (red), 2 m
- Test tip (black)
- Test tip (red)
- Crocodile clip (black)
- Crocodile clip (red)
- PC SW Multi Link with RS 232 cable
- Protective bag for accessories
- Instruction manual
- Production verification data
- Declaration of conformity
- Declaration of warranty

## Optional accessories



- INS / SUB adapter (for connection of CLASS II equipment)
- Adapter for hard connection (for all hard wired equipment)
- Continuity extension - 10 m, set of 2 pcs

Order No:

**A 1095**

**A 1096**

**S 2012**



**Measuring and Regulating Equipment Manufacturer**

Horjul 188, 1354 Horjul - SLOVENIA

Tel.: +386 1 75 58 200; Fax: +386 1 75 49 226

Internet: <http://www.metrel.si>; E-mail: [metrel@metrel.si](mailto:metrel@metrel.si)

Subject to technical change without notice!

Distributor: