

Data Sheet

ICM 2000

AC/DC Clamp Meter

FEATURES :

- Accurate DC/AC digital clamp meter for current
- DC 2500A, AC 2100A (True RMS)
- Auto-range for A, V, and Ω
- One touch zero for DCA adjustment
- Easy single rotary switch
- Continuity with buzzer
- Max/Min, Data Hold functions
- Large 3 3/4 digits LCD

SPECIFICATIONS :

DC Current:

Range	Resolution	Accuracy (of rdg)	Overload Protection
400A	0.1A	$\pm 1.5\% \pm 3$ dgts	DC 3000A
0 – 2000A	1A	$\pm 1.5\% \pm 3$ dgts	DC 3000A
2000 – 2500A	1A	$\pm 2.0\% \pm 3$ dgts	DC 3000A

AC Current: (True RMS, Crest Factor < 4)

Range	Resolution	Accuracy (of rdg)		Overload Protection
		50/60 Hz	40 - 1KHz	
400A	0.1A	$\pm 1.5\% \pm 5$ dgts	$\pm 2.0\% \pm 5$ dgts	AC 3000A
0 – 1000A	1A	$\pm 2.0\% \pm 5$ dgts	$\pm 2.5\% \pm 5$ dgts	AC 3000A
1000 – 2100A	1A	$\pm 2.5\% \pm 5$ dgts	$\pm 3.0\% \pm 5$ dgts	AC 3000A

Current Analog Output:

Range	Output	Accuracy	Overload Protection
0 - 400A	1mV/A	$\pm 2.5\% \pm 0.5$ A	600V AC
400 - 2100A	1mV/A	$\pm 2.5\% \pm 5$ A	600V AC

Frequency: (Hz, Overload Protection 600VAC, Sensitivity selected by RANGE button)

Range	Resolution	Accuracy	Sensitivity
100Hz - 1000KHz	0.01Hz - 10Hz	$\pm 0.5\% \pm 2$ dgts	10V



ISO-TECH

Data Sheet

ICM 2000

AC/DC Clamp Meter

SPECIFICATIONS :

DC Voltage: (Auto range & Manual, Overload Protection 800VAC for all ranges)

Range	Resolution	Accuracy (of rdg)	Input Impedance
400mV	0.1mV	$\pm 1.5\% \pm 3\text{dgts}$	10M Ω
4V	0.001V	$\pm 1.5\% \pm 3\text{dgts}$	5M Ω
40V	0.01V	$\pm 1.5\% \pm 3\text{dgts}$	5M Ω
400V	0.1V	$\pm 1.5\% \pm 3\text{dgts}$	5M Ω
600V	1V	$\pm 1.5\% \pm 3\text{dgts}$	5M Ω

AC Voltage: (TRMS, Crest Factor<4, Auto range & Manual, Overload Protection 800VAC)

Range	Resolution	Accuracy (of rdg)		Input Impedance
		50/60 Hz	40 - 1KHz	
400mV	0.1mV	-----	-----	-----
4V	0.001V	$\pm 1.5\% \pm 5\text{dgts}$	$\pm 2.0\% \pm 5\text{dgts}$	5M Ω
40V	0.01V	$\pm 1.5\% \pm 5\text{dgts}$	$\pm 2.0\% \pm 5\text{dgts}$	5M Ω
400V	0.1V	$\pm 1.5\% \pm 5\text{dgts}$	$\pm 2.0\% \pm 5\text{dgts}$	5M Ω
600V	1V	$\pm 1.5\% \pm 5\text{dgts}$	$\pm 2.0\% \pm 5\text{dgts}$	5M Ω

Resistance Ω : (Auto range & Manual, Open Circuit Voltage $\leq 0.5\text{V}$)

Range	Resolution	Accuracy (of rdg)	Overload Protection
400 Ω	0.1 Ω	$\pm 1.5\% \pm 3\text{dgts}$	600VAC
4K Ω	1 Ω	$\pm 1.5\% \pm 3\text{dgts}$	600VAC
40K Ω	10 Ω	$\pm 1.5\% \pm 3\text{dgts}$	600VAC
400K Ω	100 Ω	$\pm 1.5\% \pm 3\text{dgts}$	600VAC
4M Ω	1K Ω	$\pm 1.5\% \pm 3\text{dgts}$	600VAC
40M Ω	10K Ω	$\pm 1.5\% \pm 3\text{dgts}$	600VAC



ISO-TECH

Data Sheet

SPECIFICATIONS :

Resistance (Ω) and Continuity: (open voltage 0.4V)

Range	Resolution	Accuracy	Beeping	OL Protection
40-400 Ω	0.1 Ω	$\pm 1.0\%rdg \pm 2dgts$	< 40.0 Ω (approx.)	AC 600V

Diode Test:

Range	Resolution	Accuracy	Overload Protection
3V	0.001V	$\pm 2.5\% \pm 5dgts$	600V AC

Conductor Size:	Cable $\Phi 55mm$. (approx.), Bus Bar 65 x 24mm
Battery Type:	9V
Display:	3 3/4 LCD with 40 seg. bargraph
Range Selection:	Auto and manual
Sampling Time:	2 times/sec. (display); 20 times/sec. (bargraph)
Overload Indication:	Left most digit blinks
Low battery Indication:	<input type="checkbox"/> B <input type="checkbox"/>
Power Consumption:	12mA (approx.)
Operating Environment:	4°C to 50°C, less than 85% relative
Storage Environment:	-20°C to 60°C, less than 75% relative
Dimension:	271 x 112 x 46mm
Weight:	647g (battery included)



ISO-TECH