

METRA HIT 16I and 16T

Analog-Digital Multimeter with Insulation Measurement

3-348-972-03
6/1.04

- **Insulation resist. measurement:** 16I: 500 V/1000 V, 16T: 100 V
- **Multifunctional multimeter** (V, Ω, μF, Hz)
- AC and AC+DC TRMS measurement
- **Input resistance** for voltage measurement adjustable between 10 MΩ and 1 MΩ
- **Scaled current measurement** from 10 mA to 100 A with accessory clip-on current sensor
- **Precision temperature meter** °C, °F, for Pt100 and Pt1000 sensors
- **Acoustic signals** for:
 - Continuity testing
 - Dangerous contact voltages
 - Violation of overrange limits
 - Falling below generally valid limit values for insulation resistance measurement
- **Storage of min/max values**
- **Rugged, reliable design, protective rubber cover as standard equipment and ABS (Automatic Blocking System for 16I)**
- **Windows software** for graphic representation of measured values and calibration via accessory RS232 interface



- **Calibration Certificate**
as a standard feature

Multimeter with Insulation Measurement

METRA HIT 16I and 16T multimeters allow for insulation resistance measurement with a test voltage of 500 V or 1000 V for the METRA HIT 16I, or 100 V for the METRA HIT 16T in addition to multimeter functions. The METRA HIT 16I includes the V_{1MΩ} selector switch position. Capacitive DUTs can be discharged with this function, and display errors due to capacitive coupling during voltage measurements can be curtailed.

RMS Value with Distorted Waveform

The measuring process allows for TRMS measurement independent of the waveform for periodic quantities (AC) and pulsating quantities (AC and DC).

Display of Negative Values at the Analog Scale

Negative values are also displayed at the analog scale for zero-frequency quantities, so that fluctuations of the measured quantity at the zero point can be observed.

Automatic/Manual Measuring Range Selection

Quantities to be measured are selected with the rotary switch. The measuring range can either be matched automatically to the measurement value, or selected manually.

Automatic Measurement Value Storage

The stabilized measurement value is automatically retained by the DATA HOLD function. A patented process assures that the actual measurement value is stored rather than a random value, even when rapid changes to the measured quantity occur. The stored measurement value appears at the digital display. The display of current measurement values is continued at the analog scale.

IEC 61010-1, 2nd Edition

Multimeters manufactured as from 1st January, 2004 must not cause any hazards during application in any possible combination of indicated input voltages, function and range settings. Potential hazards include electric shock, fire, sparking and explosion.

Calibration

METRA HIT 16I and 16T multimeters are shipped with DKD calibration certificates. In addition to standard electrical quantities, our DKD calibration laboratory is also accredited for high value resistance of up to 30 GΩ/1000 V.

Multimeters can be re-calibrated in our DKD calibration laboratory after expiration of the customer selected calibration interval (manufacturer recommended interval of 1 year).

Guarantee

3 years material and workmanship.

Standards for Use as Insulation Measuring Instrument

EN 61557-1 VDE 0413 Part 1 EN 61557-2 VDE 0413 Part 2	Equipment for testing, measuring or monitoring of protective measures – Insulation resistance
--	---

METRA HIT 16I and 16T

Analog-Digital Multimeter with Insulation Measurement

Characteristic Values

Measuring Function	Measuring Range	Resolution	Input Impedance	Digital Display Inherent Deviation ±(...% of rdg. +... digit) at reference conditions	Overload Capacity ³⁾ Value	Duration
V =	30.00 mV	10 µV	>10 GΩ // <40 pF	0.5 + 3 ⁴⁾	600 V DC AC eff sine	continuous
	300.0 mV	100 µV	>10 GΩ // <40 pF	0.5 + 3		
	3.000 V	1 mV	11 MΩ // <40 pF	0.25 + 1		
	30.00 V	10 mV	10 MΩ // <40 pF	0.25 + 1		
	300.0 V	100 mV	10 MΩ // <40 pF	0.25 + 1		
	600 V	1 V	10 MΩ // <40 pF	0.35 + 1		
V ~¹⁾	3.000 V	1 mV	11 MΩ // <40 pF	1.0 + 3 (> 10 digits)	600 V DC AC eff sine	continuous
	30.00 V	10 mV	10 MΩ // <40 pF			
	300.0 V	100 mV	10 MΩ // <40 pF			
	600 V	1 V	10 MΩ // <40 pF			
V ≈¹⁾	3.000 V	1 mV	11 MΩ // <40 pF	1.0 + 3 (> 10 digits)	600 V DC AC eff sine	continuous
	30.00 V	10 mV	10 MΩ // <40 pF			
	300.0 V	100 mV	10 MΩ // <40 pF			
	600 V	1 V	10 MΩ // <40 pF			
A ~ ∞²⁾	30/100 A	10/100 mA	—	2.5 + 3 (> 10 digits)	120 A	continuous
			open-circuit voltage			
Ω	30.00 Ω	10 mΩ	max. 3.2 V	0.5 + 3 ⁴⁾	600 V DC AC eff sine	max. 10 s
	300.0 Ω	100 mΩ	max. 3.2 V	0.5 + 3		
	3.000 kΩ	1 Ω	max. 1.25 V	0.4 + 1		
	30.00 kΩ	10 Ω	max. 1.25 V	0.4 + 1		
	300.0 kΩ	100 Ω	max. 1.25 V	0.4 + 1		
	3.000 MΩ	1 kΩ	max. 1.25 V	0.6 + 1		
	30.00 MΩ	10 kΩ	max. 1.25 V	2.0 + 1		
►	2.000 V	1 mV	max. 3.2 V	0.25 + 1		
			discharge resistance	U ₀ max		
F	30.00 ⁹⁾ nF	10 pF	250kΩ	2,5 V	600 V DC / AC eff sine	max. 10 s
	300.0 nF	100 pF	250kΩ	2,5 V		
	3.000 µF	1 nF	25 kΩ	2,5 V		
	30.00 ⁹⁾ µF	10 nF	25 kΩ	2,5 V		
			f _{min} V =	f _{min} V ~		
Hz	300.0 Hz	0.1 Hz	1 Hz	45 Hz	≤ 600 V ≤ 300 V ≤ 30 V	continuous
	3.000 kHz	1 Hz	1 Hz	45 Hz		
	30.00 kHz	10 Hz	10 Hz	45 Hz		
	100.0 kHz	100 Hz	100 Hz	100 Hz		
°C	Pt 100 -200.0 ... +200.0 °C	0.1 °C	—	—	600 V DC AC eff sine	max. 10 s
	+200.0 ... +800.0 °C	0.1 °C	—	—		
	Pt 1000 -100.0 ... +200.0 °C	0.1 °C	—	—		
	+200.0 ... +800.0 °C	0.1 °C	—	—		
°F	Pt 100 -300.0 ... +400.0 °C	0.1 °F	—	—	600 V DC AC eff sine	max. 10 s
	+400.0 ... +999.0 °C	0.1 °F	—	—		
	Pt 1000 -145.0 ... +400.0 °C	0.1 °F	—	—		
	+400.0 ... +999.0 °C	0.1 °F	—	—		

¹⁾ TRMS measurement

²⁾ Measurement with type WZ12B clip-on current sensor

³⁾ At -20 °C ... +40 °C

⁴⁾ Without zero setting + 35 digits

⁵⁾ Without zero setting + 50 digits

^{6),7)} Range ⁶⁾ 3 V ≈: U_E = 1.5 V_{eff/rms} ... 100 V_{eff/rms} ⁷⁾ U_E = 2.5 V_{eff} ... 30 V_{eff}

⁶⁾ 30 V ≈: U_E = 15 V_{eff/rms} ... 300 V_{eff/rms} ⁷⁾ U_E = 25 V_{eff} ... 30 V_{eff}

⁶⁾ 300 V ≈: U_E = 150 V_{eff/rms} ... 600 V_{eff/rms} —

⁸⁾ Without probe

⁹⁾ METRA HIT 16I only


METRA HIT 16I and 16T

Analog-Digital Multimeter with Insulation Measurement

Insulation Measurement

Measuring Function Switch Position		Measuring Range		Resolution	Digital Display Inherent Deviation at Reference Conditions		
16I	$V_{1M\Omega}$	0 ... 1000 V $\overline{\overline{V}}$	1 V	1	$\pm(1\% \text{ of rdg.} + 10 \text{ d})$		
	$M\Omega_{INS}$	0 ... 1000 V $\overline{\overline{V}}$	1 V	1	$\pm(1\% \text{ of rdg.} + 10 \text{ d})$		
	$M\Omega_{INS}$ ($U_N = 500 \text{ V}$)	0.100 ... 1.600 M Ω 01.40 ... 16.00 M Ω 014.0 ... 160.0 M Ω 0140 ... 1600 M Ω	1 k Ω 10 k Ω 100 k Ω 1 M Ω	100	$\pm(3\% \text{ of rdg.} + 2 \text{ d})$		
	$M\Omega_{INS}$ ($U_N = 1000 \text{ V}$)	0.100 ... 3.100 M Ω 02.80 ... 31.00 M Ω 028.0 ... 310.0 M Ω 0280 ... 3100 M Ω	1 k Ω 10 k Ω 100 k Ω 1 M Ω	100	$\pm(3\% \text{ of rdg.} + 2 \text{ d})$		
16T	$M\Omega_{INS}$	0 ... 100 V $\overline{\overline{V}}$	0.1 V	0.1	$\pm(1\% \text{ of rdg.} + 10 \text{ d})$		
	$M\Omega_{INS}$ ($U_N = 100 \text{ V}$)	000.5 ... 310.0 k Ω 0.280 ... 3.100 M Ω 02.80 ... 31.00 M Ω 028.0 ... 310.0 M Ω	1 k Ω 10 k Ω 100 k Ω	100	$\pm(3\% \text{ of rdg.} + 2 \text{ d})$		
	Meas. Function Switch Position	Nom. Voltage U_N	Open-Circuit Voltage U_o	Nom. Current I_N	Short-Circuit Current I_k	Acoustic Signal at Value	Overload Capacity Duration
	$V_{1M\Omega}$	—	—	—	—	$U > 1000 \text{ V}$	600 V $\overline{\overline{V}}$
16I	$M\Omega_{INS}$	—	—	—	—	$U > 50 \text{ V}$	600 V $\overline{\overline{V}}$
	$M\Omega_{INS}$	500 V	< 1.15 x U_N	> 1.0 mA	< 2.5 mA	$R_x < 1 \text{ M}\Omega$	600 V $\overline{\overline{V}}$
16T	$M\Omega_{INS}$	—	—	—	—	$U > 50 \text{ V}$	600 V $\overline{\overline{V}}$
	$M\Omega_{INS}$	100 V	< 1.15 x U_N	> 1.0 mA	< 1.5 mA	$R_x < 1 \text{ M}\Omega$	max. 10 s

Influencing Quantities and Influence Errors

Influenc. Quantity	Sphere of Influence	Meas. Quantity/ Measuring Range	Influence Error ¹⁾ $\pm(\dots \text{ % of rdg.} + \dots \text{ digit})$	
Temperature	$0^\circ\text{C} \dots +21^\circ\text{C}$ and $+25^\circ\text{C} \dots +40^\circ\text{C}$	30/300 mV $\overline{\overline{V}}$	1.0 + 3	
		3 ... 300 V $\overline{\overline{V}}$	0.15 + 1	
		600 V $\overline{\overline{V}}$	0.2 + 1	
		V \sim	0.4 + 2	
		30 Ω ²⁾	0.15 + 2	
		300 Ω	0.25 + 2	
		3 k Ω ... 3 M Ω	0.15 + 1	
		30 M Ω	1.0 + 1	
		30 nF ²⁾ ... 3 μF	0.5 + 2 ⁵⁾	
		30 μF	2.0 + 2	
		Hz	0.5 + 1	
		-200 ... +200 $^\circ\text{C}$	0.5 K + 2	
		+200 ... +800 $^\circ\text{C}$	0.5 + 2	
		-300 ... +400 $^\circ\text{F}$	1.0 K + 4	
		+400 ... +999 $^\circ\text{F}$	0.5 + 2	
Frequency of Meas. Quantity	15 Hz ... < 30 Hz	16I: $M\Omega_{ISO}$	0.25 + 2	
	30 Hz ... < 45 Hz	16T: $M\Omega$	0.25 + 2	
	> 65 Hz ... 400 Hz			
	> 400 Hz ... 1 kHz			
Waveform of Meas. Quantity	crest factor CF	V \sim ⁴⁾	$\pm 1\% \text{ of rdg.}$ $\pm 3\% \text{ of rdg.}$	
3)	The allowable crest factor CF for the periodic quantity to be measured depends upon the displayed value:			

- ¹⁾ For temperature: indicated error values apply per 10 K change in temperature.
For frequency: indicated error values valid as of display of 300 digits.
²⁾ With zero setting
³⁾ For unknown waveform (CF > 2): Measure with manual range selection.
⁴⁾ Except for sinusoidal waveforms
⁵⁾ METRA HIT 16T: 2+2

	Measuring Function	U_N	Nominal Range of Use	Operating Error
16I	$M\Omega_{INS}$	500 V	100 k Ω ... 1600 M Ω	$\pm 10\%$
		1000 V	100 k Ω ... 3100 M Ω	
16T	$M\Omega$	100 V	100 k Ω ... 310 M Ω	$\pm 10\%$

Influencing Qty.	Influence Range	Measuring Ranges	Influence Error
Battery Voltage	$\text{---}^* \dots < 7.9 \text{ V}$ $> 8.1 \text{ V} \dots 10.0 \text{ V}$	V $\overline{\overline{V}}$	± 2 digits
		V \sim	± 4 digits
		30 Ω /300 Ω / $^\circ\text{C}/^\circ\text{F}$	± 4 digits
		3 k Ω ... 30 M Ω	± 3 digits
		$M\Omega_{ISO}$, M Ω	± 2 digits
		nF, μF	± 1 digit
		Hz	± 1 digit
		V \simeq , Ω , $M\Omega_{ISO}$, M Ω	1x inherent deviation
Relative Humidity	75%, 3 days, device off	Hz, $^\circ\text{C}$, $^\circ\text{F}$	± 1 digit
DATA	—	—	—
MIN / MAX	—	V \simeq	± 2 digits

* As of display of the --- symbol.

Influencing Quantity	Influence Range	Measuring Ranges	Damping
Common-Mode Interference Voltage	interference max. 600 V \sim	V $\overline{\overline{V}}$	> 120 dB
	interference max. 600 V \sim 50 Hz, 60 Hz sine	3 V \sim , 30 V \sim 300 V \sim	> 80 dB > 70 dB
		600 V \sim	> 60 dB
Series-Mode Interference Voltage	interference V \sim ,	V $\overline{\overline{V}}$	> 50 dB
	respective meas. range nom. value, max. 600 V \sim 50 Hz, 60 Hz sine	—	> 110 dB

Response Time (after manual range selection)

Measured Qty./ Meas. Range	Response Time	Measured Quantity Jump Function
	Analog Display	Digital Display
V $\overline{\overline{V}}$, V \sim	0.7 s	1.5 s
30 Ω ... 3 M Ω	1.5 s	2 s
30 M Ω	4 s	5 s
—	0.7 s	1.5 s
nF, μF , $^\circ\text{C}$, $^\circ\text{F}$	max. 1 ... 3 s	from 0 to 50 % of upper range limit
300 Hz, 3 kHz	max. 2 s	from 0 to 50 % of upper range limit
30 kHz	max. 0.7 s	from 0 to 50 % of upper range limit

Reference Conditions

Ambient Temp. +23 $^\circ\text{C} \pm 2 \text{ K}$

Relative Humidity 40 % ... 60 %

Measured Quantity

Frequency 45 Hz ... 65 Hz

Measured Quantity

Waveform sine

Battery Voltage 8 V $\pm 0.1 \text{ V}$

Display

LCD display field (65 mm x 30 mm) with analog and digital display including display of unit of measure, voltage type and various special functions.

Analog

Display LCD scale with pointer

55 mm for V $\overline{\overline{V}}$;

47 mm in all other ranges

$\pm 5 \dots 0 \dots \pm 30$ with 35 scale graduations for --- , 0 ... 30 with 30 scale graduations for all other ranges

with automatic reversal

Polarity Display

METRA HIT 16I and 16T

Analog-Digital Multimeter with Insulation Measurement

Overflow Display	with triangle	Ambient Conditions
Measurement Rate	20 measurements per second, for Ω : 10 measurements per second	Operating Temp. -20 °C ... + 50 °C
Digital		Storage Temperature - 25 °C ... + 70 °C (without battery)
Display/Char. Height	7 segment characters / 15 mm	Relative Humidity ≤ 75 %, no condensation allowed
Number of Places	3½ places \leq 3100 steps	Elevation to 2000 m
Overflow Display	"OL" is displayed	Deployment indoors; outdoors: only in the specified ambient conditions
Polarity Display	"—" sign is displayed with plus pole at "L"	
Measurement Rate	2 measurements per second, for Ω and °C: 1 measurement per second	
Power Supply		
Battery	9 V flat cell battery; alkali-manganese cell per IEC 6 LR 61	Protection case: IP 50, connector jacks: IP 20 per EN 60529 VDE 0470 Part 1
Autom. Shut-Down	if measurement value remains constant and no operating elements are activated for approx. 10 minutes . Can also be switched to continuous operation.	Dimensions 84 mm x 195 mm x 35 mm
Weight		Weight approx. 0.35 kg with battery

1) Times 0.7 for interface operation

2) Battery control: automatic display of the  symbol if battery voltage falls below 7 V.

Electrical Safety

Protection Class	II per EN 61010-1:2001/VDE 0411-1:2002
Oversupply Category	II III
Nominal Voltage	600 V 300 V
Fouling Factor	2 2
Test Voltage	3.5 kV~ per EN 61010-1:2001/VDE 0411-1:2002

EMC

Product standard	EN 61326-1: 1997, EN 61326: 1997/A1: 1998
Interference Emission	EN 55022: 1998 – class B
Interference Immunity	EN 61000-4-2: 1995 <ul style="list-style-type: none"> – 4 kV/8 kV contact/atmosph. discharge – power feature A EN 61000-4-3: 1996+A1: 1998 <ul style="list-style-type: none"> – 3 V/m – power feature B

Interface

Type	RS232C, serial, per DIN 19241
Data Transmission	optical with infrared light
Baud Rate	8192 bit/s

Order Information

Designation	Type	Article Number
Multimeter with insul. measurement incl. protective rubber cover, carrying strap and KS 17 cable set for test voltage: 500/1000 V	METRA HIT 16I	M216B
for test voltage: 100 V	METRA HIT 16T	M216A
METRA HIT 16I, HC20 carrying case, KS17 cable set, TF220 temperature sensor	METRA HIT 16I-Set 1	M216E
METRA HIT 16I, HC20 carrying case, TF220 temperature sensor, WZ12B clip-on current sensor	METRA HIT 16I-Set 2	M216F
Single-channel memory pack with SI232-II memory adapter, cable and METRAwin®10/METRA-Hit® software	1-CH. Pack	GTZ 3231 020 R0001
4-channel memory pack with four SI232-II memory adapters, cable and METRAwin®10/METRA-Hit® software	4-CH. Pack	GTZ 3234 020 R0001
Memory adapter for METRA HIT S	SI232-II D)	GTZ 3242 020 R0001
2 meter long RS232 interface cable (included with Z3231)	Z3241	GTZ 3241 000 R0001
METRAwin®10/METRA-Hit® software update	Z3240	GTZ 3240 000 R0001
Pt100 temp. sensor for surface and immersion measurements, -40 ... +600 °C	Z3409	GTZ 3409 000 R0001
Pt1000 temperature sensor for measurements in gases and liquids, -50 ... +220 °C (for service applications on household appliances)	TF220	Z102A
Pt100 oven sensor, -50 ... +550 °C	TF550	GTZ 3408 000 R0001
10 adhesive PT100 temperature sensors, from -50 ... +550 °C	TS-Chipset	GTZ 3406 000 R0001
Ri adapter: 200 kΩ/230 V	R200K	Z101A
Clip-on current sensor 10 mA ... 100 A, 1 mV/10 mA, jaw opening: 15 mm dia.	WZ12B D)	Z219B
Imitation leather carrying pouch for METRA HIT and METRAmax	F829	GTZ 3301 000 R0003
Cordura belt pouch for multimeters of the METRA HIT and METRAport series	HitBag	Z115A
Imitation leather ever-ready case with cable compartment	F836	GTZ 3302 000 R0001
Ever-ready case for two METRA HIT s, two adapters and accessories	F840	GTZ 3302 001 R0001
Hard case for one METRA HIT and accessories	HC20	Z113A
Hard case for two METRA HIT s and accessories	HC30	Z113B

D) Data sheet available

Edited in Germany • Subject to change without notice • A pdf version is available on the internet