3634 Central Ave. · St. Petersburg, Florida 33711 · Phone 727-328-2818 · 800-RING-IMR · FAX 727/328-2826 · **E-mai**l: Info@imrusa.com

# **NEW**

# DIGITAL THERMOMETER DT150 / DT200

**NEW** 

#### DT150/DT200

The DT150 / DT200 digital thermometers accept type J, K or T probes to accommodate your existing process technology. Its backlight displays are easy to read, even in low-light areas. The DT200 allows you to measure two inputs simultaneously.

- Accepts K, J and T thermocouples
- Time-stamped multifunction record
- Relative function displays temperature change
- Differential temperature (DT200)
- Temperature in °C or °F
- Large, backlit display
- Latest technology

### **SPECIFICATIONS**

Power Supply	9V Alkaline battery
Probes	Type K, J or T thermocouple
Range	
Туре К	-328 to 2498°F (-200 to 1369°C)
Type J	-328 to 1400°F (-200 to 760°C)
Туре Т	-328 to 730°F (-200 to 390°C)
Accuracy	+/- 0.1% reading + 1.4°F (+0.7°C)
Resolution	0.1°F, 1°F (0.1°C, 1°C)

## **ACCESSORIES**

ACCESSORES
Standard bead probes
Air probes
Surface probes
Liquid probes
Right angle probes
Soft carrying case
Hard carrying case



#### **STANDARD**

9V battery
Standard bead probe, Type K

IMR Environmental Equipment, Inc. reserves the right to adopt technical modifications without prior notice.