

TRACEABLE MEASUREMENT CAPABILITY

MEASURED QUANTITY AND RANGE	BEST MEASUREMENT CAPABILITY (\pm)	REMARKS
<u>DC RESISTANCE</u>		
1 m Ω - 1 M Ω	(15 ppm + 0.15 m Ω)	
1 M Ω - 10 M Ω	40 ppm	
10 M Ω - 1 G Ω	4 ppm/M Ω	
1 G Ω	0.5 %	
10 G Ω	0.5 %	
100 G Ω	0.5 %	
1 T Ω	0.5 %	
		SOURCING CAPABILITY ONLY @ 100 V, 250 V & 500 V
<u>DC VOLTAGE</u>		
0 – 200 mV	(18 ppm + 3 μ V)	
200 mV – 2 V	(7 ppm + 3 μ V)	
2 V – 20 V	(5 ppm + 11 μ V)	
20 V – 200 V	(8 ppm + 200 μ V)	
200 V – 1000 V	(13 ppm + 1.5 mV)	
1 kV – 25 kV	0.5 %	
<u>DIRECT CURRENT</u>		
10 μ A	55 ppm	
100 μ A	55 ppm	
1 mA	55 ppm	
10 mA	60 ppm	
100 mA	75 ppm	
1 A	110 ppm	
		SPECIFIC VALUES
0 μ A – 200 μ A	(80 ppm + 5 nA)	
200 μ A – 2 mA	(80 ppm + 4 nA)	
2 mA – 20 mA	(80 ppm + 50 μ A)	
20 mA – 200 mA	(80 ppm + 2 μ A)	
200 mA – 2 A	(100 ppm + 25 μ A)	
2 A – 10 A	0.035 %	
10 A – 20 A	0.05 %	
20 A – 50 A	0.1 %	

TRACEABLE MEASUREMENT CAPABILITY

MEASURED QUANTITY AND RANGE	FREQUENCY	BEST MEASUREMENT CAPABILITY (\pm)	REMARKS
<u>ALTERNATING VOLTAGE</u>			
30 μ V – 1 V	10 kHz – 500 MHz	3.75 %	
30 μ V – 1 V	500 MHz – 1 GHz	6.25 %	
10 mV – 100 mV	40 Hz – 4 kHz	0.04 %	
100 mV – 1000 V	40 Hz – 4 kHz	0.03 %	
200 mV – 200 V	4 kHz – 40 kHz	0.04 %	
200 mV – 2000 V	40 kHz – 100 kHz	0.04 %	
20 V – 200 V	1 kHz – 100 kHz	0.1 %	
200 V – 1000 V	1 kHz – 30 kHz	0.1 %	
10 mV – 200 mV	40 Hz – 1 kHz	(0.05 % + 5 μ V)	SOURCING ONLY
10 mV – 200 mV	1 kHz – 10 kHz	(0.06 % + 5 μ V)	
10 mV – 200 mV	10 kHz – 100 kHz	(0.09 % + 5 μ V)	
200 mV – 1 kV	40 Hz – 30 kHz	0.015 %	
200 mV – 20 V	30 kHz – 100 kHz	0.015 %	
<u>ALTERNATING CURRENT</u>			
20 μ A – 200 mA	40 Hz – 1 kHz	0.02 %	MEASUREMENT ONLY
200 mA – 2 A	40 Hz – 1 kHz	0.03 %	
2 A – 50 A	40 Hz – 1 kHz	0.2 %	
<u>FREQUENCY</u>			
1 mHz – 100 kHz		(2 parts in 10^7 + 30 μ Hz)	
100 kHz – 1 MHz		2 parts in 10^7	
1 MHz – 1 GHz		2 parts in 10^8	
<u>TIME/PERIOD</u>			
> 100 ns		2 parts in 10^7 to 0.5 %	
<u>RISETIME</u>			
1 ns – 20 ns		60 ps	SOURCING ONLY

TRACEABLE MEASUREMENT CAPABILITY

MEASURED QUANTITY AND RANGE	FREQUENCY	BEST MEASUREMENT CAPABILITY (\pm)	REMARKS
<u>AC POWER</u> 1 μ W – 100 mW	10 MHz – 18 GHz	2.5 %	50 Ω SYSTEM
<u>MODULATION</u> CARRIER FREQUENCY 3 MHz – 1.5 GHz			
AM 0 % - 100 %	50 Hz – 30 kHz	1 %	
FM 0 kHz – 150 kHz	50 Hz – 30 kHz	1 %	
<u>ATTENUATION</u> + 60 dB to - 60 dB	40 Hz – 100 kHz	0.2 %	
0 dB to - 60 dB	10 kHz – 500 MHz	3.75 %	
0 dB to -100 dB	3 MHz – 18 GHz	0.005 dB/10 dB	
- 100 to -120 dB	3 MHz – 18 GHz	0.005 dB/10 dB	
<u>PHASE</u> 0 ° - 360 °	10 Hz – 100 kHz	0.1 °	
<u>DISTORTION</u> 0.003 % - 100 %	10 Hz – 10 kHz	0.2 dB	
0.003 % - 100 %	10 kHz – 100 kHz	1.5 dB	
<u>CAPACITANCE</u> 1 pF – 160 μ F	1 kHz	(0.1 % + 0.01 pF)	
100 pF – 1 μ F	1 kHz	(0.03 % + 0.5 pF)	<u>SOURCING ONLY</u>
<u>INDUCTANCE</u> 0 – 1600 H	1 kHz	(0.1 % + 0.1 μ H)	
1 μ H – 1 H	1 kHz	(0.03 % + 0.15 μ H)	<u>SOURCING ONLY</u>
<u>TEMPERATURE</u> Electrical Calibration: Thermocouples PRT's		0.2 °C 0.02 °C	
System Calibration: -20 °C to 100 °C		0.13 °C	
100 °C to 300 °C		0.8 °C	
300 °C to 500 °C		1 °C	
Nominal 20 °C (Ambient)		0.06 °C	

TRACEABLE MEASUREMENT CAPABILITY

MEASURED QUANTITY AND RANGE	FREQUENCY	BEST MEASUREMENT CAPABILITY (±)	REMARKS
<u>TORQUE</u>			
0.2 Nm – 1 Nm		1.0 %	
1 Nm – 10 Nm		0.25 %	
10 Nm – 1000 Nm		1.0 %	
<u>OIL PRESSURE</u>			
10 lb/in ² – 12000 lb/in ²		0.1 %	
<u>GAS PRESSURE</u>			
1 bar – 40 bar		0.1 %	
<u>RELATIVE HUMIDITY</u>			
23 % RH		2.5 % RH	
54 % RH		2.5 % RH	
75 % RH		2.5 % RH	
<u>GAS</u>			
<u>CONCENTRATION</u>			
CO (Carbon Monoxide)			
50 ppm		2 % CONCENTRATION	
100 ppm		2 % CONCENTRATION	
400 ppm		2 % CONCENTRATION	
500 ppm		2 % CONCENTRATION	
O ₂ (Oxygen)			
5 %		2 % CONCENTRATION	
10 %		2 % CONCENTRATION	
15 %		2 % CONCENTRATION	
CH ₄ (Methane)			
50 ppm		2 % CONCENTRATION	
80 ppm		2 % CONCENTRATION	
0.25 %		2 % CONCENTRATION	
2.5 %		2 % CONCENTRATION	
50 %		2 % CONCENTRATION	
<u>CRIMP PULL TESTS</u>			
Up to – 250 N		0.2 N	
<u>SCALES</u>			
Up to – 300 kg		0.001 %	